



Europäisches Patentamt
European Patent Office
Office européen des brevets

Publication number:

**0 374 323
A1**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 88312239.2

(51) Int. Cl.⁵: C10J 3/48

(22) Date of filing: 22.12.88

A request for correction of the description has been filed pursuant to Rule 88 EPC. A decision on the request will be taken during the proceedings before the Examining Division (Guidelines for Examination in the EPO, A-V, 2.2).

(43) Date of publication of application:
27.06.90 Bulletin 90/26

(84) Designated Contracting States:
DE FR GB IT SE


(71) Applicant: **TEXACO DEVELOPMENT CORPORATION**
2000 Westchester Avenue
White Plains, New York 10650(US)

(72) Inventor: **Den Bleyker, Alfred Leonard**
1605 Turnpike
Houston TX 77008(US)

(74) Representative: **Ben-Nathan, Laurence Albert et al**
Urquhart-Dykes & Lord 91 Wimpole Street
London W1M 8AH(GB)

(54) Improved quench ring for a gasifier.

(57) Gasifier (10) for combusting a carbonaceous fuel to produce a usable gas and comprising an insulated outer shell (11). A combustion chamber (12) within the shell receives a fuel mixture from a fuel injection burner (14). The products of combustion, including hot produced gas, are passed through a constricted throat (23) to be cooled in a liquid bath (21). A dip tube (24) which guides the hot products into the bath, is provided with a stream of coolant from a quench ring (30). The quench ring (30) is supported on the dip tube upper end and conformed at its exposed face to minimize the effects of the hot product gas, thereby avoiding the establishment of stress points in the ring structure.



EP 0 374 323 A1

IMPROVED QUENCH RING FOR A GASIFIER

BACKGROUND OF THE INVENTION

In the production of a usable synthetic gas by the combustion of a carbonaceous fuel mixture, the process is conducted most effectively under a high temperature and high pressure conditions. For example, for the production of a gas from a carbonaceous fuel such as particulated coal, coke, or even oil, a preferred operating temperature range of about 2,000-3,000° F is maintained at a pressure of between about 5 to 250 atmospheres. The harsh operating conditions experienced in such a process, and in particular the wide temperature variations encountered, impose a severe strain on many segments of the gasifier or reactor and associated equipment.

The invention is addressed to an improvement in the structure of a gasifier, and particularly in the quench ring and the dip tube arrangement. The latter by their functions, are exposed to the gasifier's severest temperature conditions by virtue of the hot produced gas or effluent which contacts these members as the gas passes from the reaction chamber.

With respect to the prior art, U.S.P. 4,218,423 issued on August 19, 1980 in the name of Robin et al., illustrates one form of quench ring and dip tube which can be improved through use of the present arrangement. U.S.P. 4,444,726, issued on April 24, 1984 in the name of Crotty et al., also illustrates a dip tube and quench ring for a reactor vessel. In the latter, a portion of the gasifier's cooling system is insulated, but does not provide an effective means to avoid or minimize the detrimental effects that could result due to the intimate contact between the hot effluent gas and the quench ring.

Among the problems encountered due to the high temperature conditions within the gasifier, is the appearance of thermal strains which often develop in the quench ring which conducts cooling water. These strains develop as a result of the ring's close proximity to the hot effluent stream, a position which necessitates cooling. The usual problems are manifested in the form of cracks and fissures which occur in parts of the quench ring, predominately in areas where sudden transitions are present. In the latter, physical and thermal strains would be magnified and ultimately result in undesired leakage of liquid coolant.

Brief Description of the Invention

Toward overcoming the stated deficiencies in

gasifiers of the type contemplated, there is disclosed a gasifier quench ring having an internal, water circulating channel. The latter is defined in one embodiment by an appendage which extends from the inner side of the quench ring body, and which is enclosed by an external cover or closure plate thereby forming a water distribution ring or manifold. The coolant carrying channel covers the entire inner wall of the distribution ring whose external surface is exposed to the hot effluent, and is maintained in full condition. Said channel conducts a rapid flow of the water which is subsequently discharged against the dip tube guide face. The latter step facilitates effluent flow between the gasifier reaction chamber and the liquid bath.

Stated alternately, there is presently provided a reactor for gasifying a carbonaceous fuel mixture to produce a hot effluent comprising residual slag and at least one useful synthetic gas. The reactor includes a reaction chamber in which a fuel mixture is gasified, the floor of said chamber being shaped to permit an outflow of liquefied slag.

A quench chamber holding a water bath is positioned in the reactor lower section to receive and cool the hot effluent. A throat communicating the reaction chamber with the quench chamber directs a stream of the effluent into a dip tube. Said tube, in the usual manner, defines a guide passage to conduct the effluent into the water bath.

A toroidal shaped quench ring in the gasifier incorporates a distribution ring which is positioned above the dip tube to direct streams of the cooling water against the dip tube's guide surface.

The quench ring includes a body which defines a chamber or manifold communicated with a pressurized source of water. The manifold communicates in turn with a contiguously positioned distribution ring which receives and circulates the water through an annular coolant channel. The rapid flow of water through said channel due to its constricted passage, serves to stabilize and cool the quench ring outer wall which is exposed to the high temperature effluent.

The circulating water is then distributed against the dip tube guide surfaces which contact the hot effluent flow.

It is therefore an object of the invention to provide an improved gasifier for producing a usable synthetic gas, in which a gasifier dip tube is wetted by a quench ring which embodies an internal water circulatory system.

A further object is to provide a liquid carrying quench ring for a gasifier, which ring is protected from exposure to the hot effluent produced by the gasification process through means of an internal

water circulating channel.

A still further object is to provide a quench ring of the type contemplated which embodies an efficient internal cooling system to reduce development of thermally induced strains in the ring's metallic structure.

DESCRIPTION OF THE DRAWINGS

Figure 1 is a vertical elevation view in cross-section of a gasifier reactor of the type contemplated.

Figure 2 is a segmentary enlarged view of the internally channelled quench ring in Figure 1.

Figure 3 is a segmentary enlarged view taken along line 3-3 in Figure 2.

Briefly stated, in achieving the above objectives, and referring to Figure 1, there is provided a gasifier or reactor vessel for gasifying a carbonaceous fuel mixture either solid, liquid or gaseous. The gasification process, by way of partial oxidation, produces a hot effluent which includes at least one useful synthetic gas, and a residue normally in the form of particulated ash, when the fuel is a solid such as coal or coke. The gasifier is enclosed in a heavy wall, upright steel shell which is positioned to form a downflowing stream of the hot effluent which includes the produced synthesis gas.

A reaction chamber within the shell receives a pressurized stream of a fuel mixture by way of a fuel injection burner. The latter is communicated with a source of the carbonaceous fuel, as well as with a source of a gasification supporting medium such as oxygen or air to form a combustible mixture.

The products of gasification, or the hot effluent which is generated in the reaction chamber, is discharged through the reaction chamber floor to be cooled in a liquid holding quench chamber.

To facilitate passage of the hot effluent as it leaves the reaction chamber, a dip tube is positioned to guide the hot stream into the liquid bath. The dip tube, oriented in a generally upright position, is supported by a liquid conducting quench ring which directs a stream or streams of water along the dip tube's exposed guide face or effluent contacting wall.

Referring to Figure 1, a gasifier or reactor vessel of the type contemplated embodies an elongated metallic steel wall shell 11. The gasifier reactor is normally operated in an upright position to form a downflowing stream of produced product. Shell 11 includes a reaction chamber 12 at the upper end to withstand the expected high operating temperatures between about 2,000 to 3,000° F. Chamber 12 is provided with a lined multi-layer

inner wall 13 preferably formed of a suitable refractory material.

A burner 14 is removably positioned at shell 11 upper wall or roof to inject the carbonaceous fuel mixture such as particulated coal or coke, from a source 16, into reaction chamber 12. An amount of the gasification supporting medium from a pressurized source 17 is concurrently fed into burner 14 as a part of the fuel mixture.

The invention can be applied equally as well to gasifiers which burn a variety of carbonaceous solid, liquid, or gaseous fuels. To illustrate the instant embodiment, it will be assumed that burner 14 is communicated with a source 16 of coke. The latter is preferably preground and formed into a slurry of desired consistency by the addition of a sufficient amount of water. The pressurized gas at source 17 is normally oxygen, air or a mixture thereof.

The lower end of reaction chamber 12 is defined by a downwardly sloping refractory floor 18. This configuration enhances the discharge of the hot gas, and particularly liquefied effluent from reaction chamber 12.

The lower end of shell 11 encompasses a quench chamber 19 into which the products of gasification are directed. Here, both solid and gaseous products contact, and are forced into liquid bath 21 which is most conveniently comprised of water. The cooled gas then emerges from quench chamber 21 into disengaging zone 26, before leaving the gasifier by way of line 22. The cooled gas can now be processed in downstream equipment and operations into usable form. The solid or slag component of the effluent sinks through bath 21 to be removed by way of discharge port 23 into lockhopper 24.

Reaction chamber 12 and quench chamber 19 are communicated through constricted throat 27 formed in the reaction chamber floor 18. To achieve efficient contact of the hot effluent as it leaves reaction chamber 12, with the liquid in bath 21, quench chamber 19 as noted is provided with a dip tube 29. The latter includes an upper edge 31 positioned adjacent to the downstream side of constricted throat 27. Dip tube 29 further includes a lower edge 32 which terminates in the coolant bath 21.

Referring to Figure 2, constricted throat 27 defines the guide passage through which the high temperature, high pressure effluent initially passes. Cooling of the slag as well as produced gas is achieved by immersion in quench chamber 19 (Figure 1) to permit the gas to be readily handled.

However, as the hot effluent leaves the downstream side of throat 27 it will expand outwardly and be guided by the exposed exterior face of quench ring 33 wall which serves as a water distribution ring.

Functionally, the inner wall of dip tube 29 defines a cylindrical guide surface for the hot, downwardly flowing effluent, including both the gaseous and solid components which leave throat 27 in a high velocity stream. Beneficially, and to facilitate effluent flow, the inner wall or guide surface of the cylindrical dip tube 29 is wetted, as noted, by directing one or more pressurized streams of water thereagainst.

In one embodiment of quench ring 33, the latter is comprised of a toroidal metallic body 34, which is fastened by a series of bolts 36 to the lower support floor 15 of combustion chamber 12. Refractory 18 as shown, extends inwardly a sufficient distance to overhang and protect at least a part of the quench ring from direct impingement of the hot gases.

Said toroidal body 34 is shaped to define an internal annular manifold or chamber 37 for carrying the coolant water. The underside of the toroidal body 34 is provided with a plate 38 which can be removable or can be welded in place, and which accommodates at least one, and preferably a plurality of risers 39. The latter, as shown in Figure 1, are communicated with a pressurized source of the water 41 by way of conduit 42.

An inner or intermediate wall 43 of body 34 is provided with a peripheral mounting hub to which the upper end 31 of cylindrical dip tube 29 is supportably fastened. Said wall 43 is further provided along its external surface with an annular appendage comprised of a generally horizontal neck 44. An upright rim 46 extends from neck 44 to define an annular coolant circulating channel 47. Said channel 47 thereby covers and cools the entire contact face 49 of the quench ring exposed wall.

The exposed external or outer surface 51 of toroidal body 34 is provided with an effluent guide panel or cover 48 which depends therefrom, and whose internal surface 49 is spaced from said appendage 44-46 to define the narrow or constricted annular coolant channel 47.

The external, exposed face 51 of effluent guiding panel 48 is appropriately curved to facilitate passage of, and to minimize interference with the rapid downflow of the hot effluent which contacts said surface. In one embodiment, the external convex surface 51 defines an upper portion of the effluent guide stream. A lower, generally circular portion of said exposed face guides the effluent downwardly into contact with dip tube 33 contact surface. As presently shown, surface 51 can take the configuration of an arcuate or semi-circular curvature to facilitate passage of the effluent flow.

The narrow coolant channel 47 is provided at its underside with an exit or expanded reservoir 52 into which the coolant water is forced prior to its

leaving the coolant channel by way of one or more constricted discharge ports 53. In a preferred embodiment, the continuous discharge opening of 53 and 54 comprises a narrow passage defined between the downwardly extending edge of panel 48 and the dip tube 29 surface. To maintain the constricted opening 53, spacers 54 can be positioned in a manner that the opening will not, over a period of time, close.

Referring to Figures 2 and 3, to introduce water from the coolant carrying manifold 37 to constricted channel 47, one or more cross passages 56 are formed in the intermediate wall 43. Cross passages 56 extend preferably from the upper portion of manifold chamber 37, into the upper portion of the coolant channel 47. The series of cross passages 56 are preferably equispaced about the periphery of intermediate wall 43. More preferably they are arranged to provide a series of flow streams which enter coolant channel 47 substantially tangential to the channel walls whereby to induce a rapid, swirling action or flow to the coolant before it is passed downwardly into discharge port 53.

The arrangement of the coolant water flow from manifold 37 to discharge port 53 has several advantages. Primarily, the positioning of passages 56 assure that channel 47 will always be full of water. As a consequence, and due to its circular flow, the water will overflow rim 46 and contact the inner face or surface 48.

This more uniform, efficient cooling action will assure that the outer exposed face 51 will likewise be subject to cooling. The overall effect is the elimination of any part of the external, exposed face 51 or of panel 48 which will tend to develop stress cracks.

It is understood that although modifications and variations of the invention may be made without departing from the spirit and scope thereof, only such limitations should be imposed as are indicated in the appended claims.

Claims

1. A gasifier (10) for the high temperature combustion of a carbonaceous fuel to produce a usable gas, which gasifier includes an insulated shell (11) having a combustion chamber (12) in which the fuel is burned at an elevated temperature and pressure, a quench chamber (19) in said shell (11) holding a liquid bath (21) for cooling products of combustion, a constricted throat (23) communicating the respective combustion chamber (12) and quench chamber (19), an elongated dip tube (24) having an inner wall (29) which defines a flow guide path (28) between said combustion chamber (12) and said quench chamber (19), and having op-

posed upper and lower edges (26,27), a quench ring (30) supportably positioned at the upper end of said dip tube and communicated with a pressurized source of liquid coolant (38), and a drain passage (31) in the quench ring for discharging a flow of liquid coolant (30) along the dip tube inner wall (29) to wet the surface thereof, characterized in that said quench ring (30) has a curved exterior face positioned contiguous with the dip tube inner wall (29) to define a segment of the said flow guide path (28). 5 10

2. A gasifier according to Claim 1 wherein said quench ring is comprised of a torroidal shaped ring (30) having a central passage disposed outwardly adjacent to the constricted throat (23). 15

3. A gasifier according to Claim 1 or Claim 2 wherein the quench ring (30) is supported in said quench chamber (19) on said dip tube upper edge (26).

4. A gasifier according to any one of Claims 1 - 3 wherein said dip tube upper edge (26) is registered in said quench ring drain passage (31) to segregate said quench ring into inlet and discharge compartments (32,33), respectively. 20

5. A gasifier according to Claim 4 wherein said quench ring (30) includes conduit means (37) communicating said inlet compartment (32) with the pressurized source of liquid coolant (38). 25

6. A gasifier according to Claim 4 or Claim 5 wherein said dip tube upper edge (26) forms a transverse connecting passage (34) between the inlet and discharge compartments (32,33). 30

7. A gasifier according to Claim 6 wherein the dip tube upper edge (26) is serrated and engages the quench ring (30) to form said transverse liquid connecting passage (34). 35


8. A gasifier according to any one of Claims 1 - 7 including a liquid distribution ring (39) surrounding, and spaced from said quench ring (30), being communicated with said source of liquid coolant (38) and with said quench ring (30), respectively. 40



9. A gasifier according to Claim 8 wherein said quench ring (30) and distribution ring (39) define an annular space (41) therebetween

10. A gasifier according to any one of Claims 1 - 9 wherein said quench ring drain passage (31) is formed in the quench ring lower side. 45

11. A gasifier according to Claim 10 wherein said quench ring drain passage includes an up-standing rim (36) spaced from said dip tube upper edge (26) to define an elongated opening (31). 50

FIG.1.







European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 88 31 2239

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL.5)
E	US-A-4 801 306 (DENBLEYKER) * Column 2, line 10 - column 4, line 68 * -----	1-11	C 10 J 3/48
			TECHNICAL FIELDS SEARCHED (Int. CL.5)
			C 10 J
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 28-07-1989	Examiner WENDLING J. P.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document			

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.